

ULTRASONIC MP

CONTROLLED FOAM DEGREASER FOR ULTRASOUND MACHINES

ULTRASONIC MP is a controlled foam degreaser, formulated with a balanced formulation of surfactants, complexing additives and alkali, which properties are particularly suitable for removing plaque embedded grease, oil and any kind of dirt.

For its formulation based on controlled foam surfactants, is indicated for use as an industrial cleaner degreaser circuit, recirculation systems cleaning, scrubbing and cleaning machines dip ultrasound machines.

DOSAGE AND METHOD OF USE

In recirculation cleaning systems, circuits, sweeping machines and ultrasonic bath is used at a rate between 3% and 10% depending on the degree of soiling.

Do not use ULTRASONIC MP on painted surfaces, aluminum or their alloys and avoid contact with acids and other cleaners.

TECHNICAL SPECIFICATIONS

| | |
|------------|---------------------------------|
| COLOUR | BROWN |
| APPEARANCE | TRANSPARENT LIQUID |
| ODOR | CHARACTERISTIC |
| DENSITY | 1,22 +/- 0,05 g/cm ³ |
| pH 1% | 12,5 +/- 0,5 |

CONTAINS

| | |
|----------|------------------------|
| 5 – 15 % | NaOH |
| < 5 % | Nonionic surfactants |
| < 5 % | Phosphonates |
| < 5 % | EDTA and salts thereof |

This product meets the existing legislation on biodegradability and Health Technical Regulation on Detergents.